

INSTALLER SUPPLIED LOW VOLTAGE TERMINALS (24V NOMINAL)

SELECT LOW OR LINE VOLTAGE INCOMING POWER TO SCC, NOT BOTH


RELAY CONTROL WIRING TERMINALS. CONNECT TO COM & N/C. DO NOT USE SOLID CORE WIRE

INSTALLER SUPPLIED OPTIONAL LINE VOLTAGE (90-240 VAC, 50-60 HZ)

INTERNAL ELECTROCHEMICAL CO or NO₂ SENSOR



INTERNAL CATALYTIC H₂ or CH₄ or C₃H₈ SENSOR



INSIDE DOOR ESH-A

ESH-A 4-WIRE ANALOG TRANSMITTER WIRED TO SCC SELF-CONTAINED SYSTEM

THIS SCC-D-TCO-R / ESH-A COMBINATION MAKES A TWO CHANNEL GAS DETECTION SYSTEM MONITORING UP TO 5,000 SQ. FT OF SPACE FOR CO (or NO₂) AND A COMBUSTIBLE GAS (H₂ or CH₄ or C₃H₈) IN VEHICLE EXHAUST APPLICATION

CRITICAL ENVIRONMENT TECHNOLOGIES CANADA INC.
www.critical-environment.com
 SCC-D-TCO-R or SCC-D-NO2B-R
 C/W ESH-A WIRING CONNECTION
 PHOTO DRAWING
 REV-A January 21, 2016