

Top Mounted Strobe



The Top Mounted Strobe is a factory-installed option available at the time the FCS Controller is ordered. This high-powered red LED flashing beacon delivers excellent flash intensity and features a rugged, vibration-resistant design for long service life. Constructed from durable polycarbonate, it carries an IP65 rating for reliable performance in many environments.

It is ideal for refrigeration applications and, when used in conjunction with the Manual Shutoff Switch, complies with B52 code requirements. The strobe may also be employed for emergency shutdowns, ventilation purges, and similar safety-related operations.

Note: The Top Mounted Strobe provides visual indication only and does not include an audible alarm.

KEY FEATURES

- » Lightweight, durable
- » Weather and corrosion resistant
- » Excellent flash intensity
- » 4 User selectable flash patterns

APPLICATIONS

- » Parking Garages
- » Refrigeration Plants
- » Equipment/ Machinery Rooms
- » Manufacturing Plants
- » Food Processing Plants
- » Power Generation Plants
- » ... and many more

TECHNICAL SPECIFICATIONS

MECHANICAL

Enclosure	PC cover and base
Size	6.1 cm dia x 13 cm H 2.4 in dia x 5.2 in H
Lens Colour	Red
# of Flash Patterns	4

USER INTERFACE

Push Button Switch	Push to change flash patterns
--------------------	-------------------------------

ELECTRICAL

Operation Voltage	10 - 30 VDC
Power	0.3 W

ENVIRONMENTAL

Operating Temperature	-20°C to 65°C (-4°F to 149°F)
-----------------------	-------------------------------

CERTIFICATION

IP65 rated
Certification requirements are met if this device is connected to a CSA approved CET Controller, Self Contained Controller, Transmitter or a CSA approved Class 2 power supply

PRODUCT CODES (OPTION)

OPTION (Factory installed) Add at the end of the product "Part Number".

- L	Top Mounted Strobe (factory installed on Controller at time of order)
-----	---