

# Splash Guard



OPTIONS & ACCESSORIES

This Splash Guard is an optional accessory that can be added to many CETCI gas detectors to make the enclosure water and dust tight in wash down or water spray environments. We recommend a Splash Guard be used to protect the sensor where spray down of equipment is a common occurrence. The Splash Guard is factory installed over the sensor vent on the front of the enclosure to protect the sensor to exposure to water, and dust. The fluted edges on the underside allow a more open area through which gas can permeate and the ridges provide a multi-step barrier through which water cannot penetrate and reach the sensor. With the Splash Guard installed, the enclosure meets IP54 standards.

During calibration, a special calibration clip (p/n: CET-SGC) is available for use with the Splash Guard to ensure a successful calibration.

The Splash Guard may slow down the response time of the sensor during calibration, however most sensors accurately detect gas with the Splash Guard installed. A few exceptions are: Chlorine (Cl<sub>2</sub>), Chlorine dioxide (ClO<sub>2</sub>), Ozone (O<sub>3</sub>), Hydrogen chloride (HCl), Hydrogen cyanide (HCN), and Phosphine (PH<sub>3</sub>) sensors. These are considered to be "sticky gases" that adhere to this Splash Guard and the enclosure vent instead of flowing freely through to the sensor. Therefore, the sensor is not able to accurately detect gas. Units with sticky gas sensors may be ordered with the Splash Guard for sticky gases (Option -SN).

## KEY FEATURES

- » Protects sensor and interior of enclosure from water and dust
- » When installed, enclosure is IP54 rated
- » Ideal for washdown, water spray, wet environments or outdoor applications
- » Factory installed

## APPLICATIONS

- » Food Processing Plants
- » Wineries and Breweries
- » Wastewater Treatment Plants
- » Meat Processing Plants
- » ... and many more



## TECHNICAL SPECIFICATIONS

### MECHANICAL

<b>Material</b>	ABS/Polycarbonate blend, injection molded
<b>Size</b>	54 mm dia x 9.3 mm thick 2.13 inches dia x 0.37 inches thick

### CERTIFICATION

Device is rated IP54 with splash guard installed. Provides protection from dust that may harm the equipment and protection against water spray from all directions.

## CET COMPATIBLE PRODUCTS

CGAS-A and CGAS-D Gas Detector (except sticky gases, NO <sub>2</sub> and CO+NO <sub>x</sub> )
CGAS-A-VLT-NH3-S Ammonia Vent Line Transmitter (included)
LPT Low Power Transmitter (except CL <sub>2</sub> )
LPT-P Car Park Digital Transmitter
LPT-M Modbus® Transmitter (except sticky gases)
LPT-B BACnet® Transmitter (except sticky gases)
SCC Self Contained Controller
DCC Dual Channel Controller
ESH-A Remote Sensor

## PRODUCT CODES

**OPTION** (Factory installed) Add at the end of the product "Part Number".

<b>S</b>	Splash Guard
----------	--------------

## ACCESSORIES

<b>CET-715A-CK1</b>	Calibration Kit for 17, 34, 58, 74, 100 L cylinders, 0.5 LPM flow regulator & adapter to fit 17 L cylinder
<b>CET-SPG</b>	Calibration clip for splash guard

